



Brilliant, Large Multi-Touch Display in a Lightweight Rugged Tablet

The M9700 rugged tablet combines form and function in a lightweight mobile tablet. With an eye-catching 9.7-inch display and its rugged construction, the Windows® tablet ships ready for enterprise.

Large, brilliant display—full 9.7-inch multi-touch display for pan and zoom functions.

Windows Embedded 7 operating system—allows for seamless migration into most enterprise environments.

User-friendly form factor—delivers lightweight mobility in a rugged tablet that is just over 2 pounds (989 grams) and less than an inch thick (22 millimeters).

IP54 and meets MIL-STD-810F—Protected against water, dust, and 4-foot drops to concrete, offering a more durable solution than consumer tablets and enabling use in a variety of environments.

Multiple communications options—WLAN, Bluetooth, and optional WWAN 3G and GPS.

Accessories



Ethernet Adapter



HDMI Adapter




Vehicle Adapter



Desktop Dock



Carry Case



Charging Cart



Hand Strap

Core System	
Operating System	Windows® Embedded Standard 7
Processor	Intel® Atom™ N2600 dual core 1.6 GHz
Memory	2 GB DDR3-800 32 GB solid state drive (64 GB optional)
Display	
	9.7-inch XGA (1024 × 768) IPS LED panel 350 nits Multi-touch capacitive touchscreen (four point) Sunlight viewable (optional)
Keypad & Buttons	
	Power button Programmable Function key Menu key Volume up/down keys LED indicator (power, battery, HDD access, WiFi)
Communications	
WLAN	802.11 b/g/n
WWAN	Optional 3G module
GPS	Optional GPS module
Bluetooth®	v2.1 + EDR Class II
Input/Output	
	Power jack 1× USB 2.0 1× LIF connector (Ethernet or HDMI via dongle)
Expansion Slots	
	SIM Card slot
Data Capture	
	2 MP color camera with auto-focus and flash
Audio	
	2× 1 W speakers HD Audio 1× stereo headset jack

Software	
Windows® Embedded Standard 7	IE8, IIS 7.0, .NET 3.5, Remote Desktop, SQL, Backup and Restore CD, Boot from VHD or USB, Power Management System restore CD User Manual on CD
Power	
Battery	Internal Li-ion 5300 mAh
Input	12 VDC
Adapter	100–240 V, 50–60 Hz / 12 V DC input
Dimensions	
	10.5 (L) × 8.3 (W) × 0.8 (H) inches [267 × 210 × 22 mm] 2.18 lb. [988 g]
Regulatory	
	FCC class B CE EN60601-1-1 EN60601-1-2
Environment	
Operating temperature	32 to +122 °F [0 to +50 °C]
Charging temperature	32 to +113 °F [0 to +45 °C]
Drop	Multiple 4-foot (1.2-meter) drops to concrete
ESD	15 kV air discharge, 8 kV direct discharge
Sealing	IP54 certified
Humidity	30%–90%, non-condensing
Vibration	MIL-STD-810F

©2012 DAP Technologies. All rights reserved. DAP Technologies reserves the right to change product specifications without notice.



Solzon Corporation
119 Drum Hill Road, Suite 321
Chelmsford, MA 01824
www.solzon.com

For more information please contact us at

(855) 765-9661 or email us at sales@solzon.com.

